

# Standard electric strike

## Fail-unlocked 138



### Minimum fitting size - maximum effect

#### effeff standard electric strike 138 with FaFix (FF)

Model with basic features.

#### The advantages at a glance

- Radius keeper, FaFix 3 mm adjustable
- Universal voltage
- Compatible with all current mortise locks
- Compatible with all commercially available striking plates also striking plates for plastic profiles
- Symmetrical design. DIN left/right as well as horizontal applicable

| Electrical data                      | 12 V DC | 24 V DC |
|--------------------------------------|---------|---------|
| Rated resistance                     | 51 Ω    | 160 Ω   |
| Current consumption DC (stabilised)  | 235 mA  | 150 mA  |
| Max. keeper pre-load DC (stabilised) | 30 N    | 30 N    |

#### Characteristics

- Adjustable keeper (FF, FaFix)
- Adjustable strike (F, Fix)
- Monitoring contact (RR)
- Diode (05)
- Fail-unlocked
- Hold-open function

#### Technical attributes

- Break-in resistance
- Height
- Width
- Depth
- Operating temperature range
- Installation position
- Material housing
- Material keeper
- Fafix regulating range
- Latch bolt engaging depth
- Internal works continuous function load cycles

#### DIN directions

Universal

#### Voltage

12 V DC

24 V DC

#### Order no.

138

\*\* \*

