

Products ▾

Assemble kit

B 12V PSU for Hub/Hub Plus/ReX

More ▾

Tech specs

BASELINE

12V PSU for Hub/Hub Plus/ReX

Power supply unit for the device operation on a low-voltage power source



Device compatibility

Check

Input

Voltage

8–20 V_{DC}

Current

up to 1 A

Turn-on voltage

8 V_{DC} ± 2.5%

Turn-off voltage

6.9–7.5 V_{DC}

Depends on the load

Output

Voltage

4.65 V_{DC} ± 3%

Current

up to 1.5 A

Installation

Installation method

into the hub or range extender enclosure by replacing the bundled power supply board

Operating temperature range

from -10°C to +40°C

Operating humidity

up to 75%



Connection to the power supply network

Connector slot

6.5 × 2 mm

Power jack (female)

Connector

5.5 × 2.1 mm

Power jack (male)

Board

Colour

N/A

Dimensions

138 × 64 × 13 mm

Weight

30 g

Complete set

12V PSU for Hub/Hub Plus/ReX

Terminal adapter

Quick start guide

Certification and compliance with standards



12V PSU for Hub/Hub Plus/ReX



Additional information

[Compliance with standards](#)

[User manual](#)

[Learn more >](#)

[Learn more >](#)

Warranty

24 months

[Learn more >](#)

Subscribe

Subscribe to our emails about secure life. No spam.

[Subscribe](#)

Request extra help

✉ support@ajax.systems

🗉 [@AjaxSystemsSupport_Bot](#)

💬 [Send a request](#)



Rating 4.8

4,500,000

people worldwide under Ajax protection

💡 [Suggest a feature](#)



Products

Intrusion protection

Video surveillance

Fire and life safety

Software


Ajax Security System

Ajax PRO: Tool for Engineers

Ajax Desktop

- [Comfort and automation](#)
- [All products](#)
- [Services](#)
- [System integrations](#)
- [Ajax Ready products](#)
- [Fibra wired protocol](#)
- [Ajax radio protocols](#)

- [Ajax PRO Desktop](#)
- [Ajax TV](#)
- [Ajax Translator PRO](#)
- [Ajax Cloud Signaling](#)
- [Scenarios](#)



Solutions

- [Customer stories](#)
- [Solutions by facility type](#)
- [Commercial fire detection and alarm system](#)
- [Wireless Grade 3 solution](#)
- [Video surveillance solution](#)
- [Integration with Yale smart locks](#)
- [Upgrades and retrofits](#)
- [Why Ajax](#)
- [How it works](#)

Support

- [Manuals and articles](#)
- [Compliance with standards](#)

Tools

- [Ajax device compatibility](#)
- [CMS software compatibility](#)
- [Ajax Services availability](#)
- [Video storage calculator](#)
- [Video device calculator](#)
- [Battery life calculator](#)
- [Radio communication range calculator](#)
- [Switches and outlets configurator](#)
- [Fibra power supply calculator](#)
- [All web tools](#)

Monitoring solutions and integrations

- [Intrusion alarm monitoring](#)
- [Video monitoring and visual alarm verification](#)
- [Audio alarm verification](#)


Company

- [Blog](#)
- [About us](#)
- [Press page](#)
- [Events](#)
- [Career](#)
- [Ajax Next](#)

For partners

- [For partners](#)
- [Ajax Academy](#)
- [Partner Portal](#)

[Reviews and feedback](#)

 [Србија](#) [Privacy policy](#) [Report a vulnerability](#) [GDPR White Paper](#) [NDAA Statement](#) [Cookie policy](#)
[Anti-Spam Policy](#) [Ajax Services T&C](#) [End user agreement](#) [Warranty](#)

© 2026 AJAX SYSTEMS CH. All rights reserved