

FIBRA-LINESUPPLY-45W-B

Ajax



Features

- Ajax Fibra
- Module for additional power supply of Fibra lines
- Fibra Protocol
- Grade 3 approved
- Bidirectional
- Extends the range of the bus line to 2000 m
- 1 input line and 1 output line
- Can be installed anywhere on the bus
- Up to 10 LineSupply per bus
- Connector for a 12 V battery
- Main supply to 230 VAC
- Tamper connector
- Output power of 45 W
- Compatibility with Hub Hybrid (2G and 4G)
- Black colour

Specifications

Brand	Ajax Fibra
Security grade	Grade 3
Transmission distance	Up to 2000 m (Recommended): twisted pair U/UTP cat. 5)
Bus connection	4 wire cable
Tamper-resistant opening	Available (connected to the housing)
Number of output lines	1
Number of input lines	1
Main power supply	230 VAC
Backup battery	Connector for 12 VDC battery with a capacity of 7 to 18 Ah
Output power	30 W for the Fiber bus output and 15 W for the backup battery. Total 45 W of output power
Modules per bus	Up to 10 modules per bus
Ventilation	Passive ventilation system
Protection	Surge and short-circuit protection
Compatibility	Compatible with Hub Hybrid (2G and 4G)
Compatible housings	FIBRA-CASE-C260-W y FIBRA-CASE-D430-W
Temp. operation	-10 °C ~ 40 °C
Dimensions	85 (H) x 160 (W) x 53 (D) mm
Weight	456 g
Colour	Black