

# FIBRA-LINESUPPLY-75W-B

Ajax



## Features

---

- Ajax Fibra
- Module for additional power supply of Fibra lines
- Fibra Protocol
- Grade 3 approved
- Bidirectional
- Extends the range of the bus line to 2000 m
- 1 input line and 2 output lines
- Can be installed anywhere on the bus
- Up to 10 LineSupply per bus
- Connector for a 12 V battery
- Main supply to 230 VAC
- Tamper connector
- Output power of 75 W
- Compatibility with Hub Hybrid (2G and 4G)
- Black colour

## Specifications

---

<b>Brand</b>	Ajax Fibra
<b>Security grade</b>	Grade 3
<b>Transmission distance</b>	Up to 2000 m (Recommended): twisted pair U/UTP cat. 5)
<b>Bus connection</b>	4 wire cable
<b>Tamper-resistant opening</b>	Available (connected to the housing)
<b>Number of output lines</b>	2
<b>Number of input lines</b>	1
<b>Main power supply</b>	230 VAC
<b>Backup battery</b>	Connector for 12 VDC battery with a capacity of 7 to 18 Ah
<b>Output power</b>	30 W per Fibra bus output and 15 W for battery back-up. Total 75 W of output power.
<b>Modules per bus</b>	Up to 10 modules per bus
<b>Ventilation</b>	Passive ventilation system
<b>Protection</b>	Surge and short-circuit protection
<b>Power</b>	AC 110~240 V, 50/60 Hz
<b>Compatibility</b>	Compatible with Hub Hybrid (2G and 4G)
<b>Compatible housings</b>	FIBRA-CASE-C260-W y FIBRA-CASE-D430-W
<b>Temp. operation</b>	-10 °C ~ 40 °C
<b>Dimensions</b>	85 (H) x 160 (W) x 53 (D) mm
<b>Weight</b>	456 g
<b>Colour</b>	Black