EP-IPT210A-2

EasyP

Features

- Easy-P with Artificial Intelligence

- Turret IP Camera

- 1/3" Progressive Scan CMOS

- 2 Megapixel (1920x1080)

- 2.8 mm fixed lens

- Minimum illumination 0.04 Lux | 0 Lux with IR

- IR Range 25 m

- DWDR

- Integrated microphone

- Full compatibility with Uniview and Hikvision

- Supports UMD and Motion Detect 2.0: advanced motion detection that is triggered only by human and/or vehicle movement

- AI: intrusion detection, motion detection based on human detection. Reduces false alarms

- ONVIF Compatible

- P2P

- PoE

- Plastic material

Specifications

Brand	EASY-P
Image sensor	1/3" Progressive Scan CMOS
Maximum resolution	2 Megapixel (1920x1080)
Minimum illumination	Colour: 0.04 Lux @(F1.6, AGC ON)
Lens	2.8 mm
Viewing Angle (FOV)	H: 95°, V: 53°, D: 114°
Lighting Scope	IR up to 25m
Day/Night	Removable mechanical ICR filter
Compression	H.264 / H.265 / JPEG / AVI / MJPEG
Electronic Shutter	1/3~1/100000 s
Main Stream rate	1920*1080@30fps 1280*720@30fps
Extra Stream rate	720*480@30fps 640*360@30fps 352*288@30fps
Bitrate	64 Kbps ~ 6 Mbps
Image improvements	WDR, BLC, HLC, 3D-DNR, AWB, ROI, Mirror Function, Privacy Mask, ROI
Motion detection and UMMD	Supports both functions
Smart Features	Native support of Motion Detect 2.0 and UMD
Audio	Integrated microphone
Audio Compression	G711A / U
Network interface	Ethernet 10 / 100M BaseT
Remote access	Web Browser, APP
Interoperability	ONVIF, plug&play with Uniview and Hikvision
P2P	Yes
Power	DC 12 V / 9 W max. PoE IEEE802.3af
Material	Plastic

Temp. operation	-20º C ~ +60º C
Dimensions	109.3 (Ø) x 95.2 (h) mm
Weight	242 g