

IP CCTV / Professional IP cameras / EASY-P / Bullet Cameras

EP-IPB110A-2

EasyP



Features

- Easy-P with Artificial Intelligence
- Bullet IP camera
- 1/3" Progressive Scan CMOS
- 2 Megapixel (1920x1080)
- 2.8 mm fixed lens
- Minimum illumination 0.04 Lux | 0 Lux with IR
- IR Range 25 m
- DWDR
- Integrated microphone
- Plastic material
- Full compatibility with Uniview and Hikvision
- Supports UMD and Motion Detect 2.0: advanced motion detection that is triggered only by human and/or vehicle movement
- AI: intrusion detection, motion detection based on human detection. Reduces false alarms
- ONVIF Compatible
- P2P
- Weatherproof IP66
- PoE

Specifications

Brand	EASY-P
Image sensor	1/3" Progressive Scan CMOS
Maximum resolution	2 Megapixel (1920x1080)
Minimum illumination	Colour: 0.04 Lux @ (F1.6, AGC ON) B/W: 0 Lux IR
Lighting Scope	IR up to 25m
Day/Night	Removable mechanical ICR filter
Electronic Shutter	1/3 ~ 1/100000 s
Lens	2.8 mm
Viewing Angle (FOV)	H: 95°, V: 53°, D: 114°
Main Stream rate	1920*1080@30fps, 1280*720@30fps
Extra Stream rate	720*480@30fps, 640*360@30fps, 352*288@30fps
Compression	H.264 / H.264+ / H.265 / H.265+ / JPEG / AVI / MJPEG
Image improvements	WDR, BLC, HLC, 3D-DNR, AWB, ROI, Mirror Function, Privacy Mask, ROI
Bitrate	64 Kbps ~ 6 Mbps
Smart Features	Native support of Motion Detect 2.0 and UMD
Motion detection and UMMD	Supports both functions
Audio	Integrated microphone
Audio Compression	G711A / U
Network interface	Ethernet 10 / 100M BaseT
Remote access	Web Browser, APP
Interoperability	ONVIF, plug&play with Uniview and Hikvision
P2P	Yes
Power	DC 12 V / 9 W max. PoE IEEE802.3af
Degree of protection	Weatherproof IP66

Material	Plastic
Temp. operation	-20° C ~ +60° C
Dimensions	174 (W) x 67.9 (H) x 69.8 (D) mm
Weight	295 g