

IP CCTV / Professional IP cameras / EASY-P / Bullet Cameras

EP-IPB120A-4

EasyP



Features

- Easy-P with Artificial Intelligence
- Bullet IP camera
- 1/3" Progressive Scan CMOS
- 4 Megapixel (2688x1512)
- 2.8mm fixed lens
- Minimum illumination 0.03 Lux | 0 Lux with IR
- IR Range 25 m
- DWDR
- Integrated microphone
- Full compatibility with Uniview and Hikvision
- Supports UMD and Motion Detect 2.0: advanced motion detection that is triggered only by human and/or vehicle movement
- AI: intrusion detection, motion detection based on human detection. Reduces false alarms
- ONVIF Compatible
- P2P
- Weatherproof IP67
- PoE

Specifications

Brand	EASY-P
Image sensor	1/3" Progressive Scan CMOS
Maximum resolution	4 Megapixel (2688*1512)
Minimum illumination	Colour: 0.03 Lux @(F1.6, AGC ON)
Lighting Scope	IR up to 25m
Day/Night	Removable mechanical ICR filter
Electronic Shutter	1/3~1/100000 s
Main Stream rate	2688*1512@25fps, 2560*1440@30fps, 1920*1080@30fps, 1280*720@30fps
Extra Stream rate	1280*720@30fps, 720*480@30fps
Compression	H.264 / H.264+ / H.265 / H.265+ / JPEG / AVI / MJPEG
Bitrate	64 Kbps ~ 6 Mbps
Lens	2.8 mm
Viewing Angle (FOV)	H: 103°, V: 55°, D: 122°
Image improvements	WDR, BLC, HLC, 3D-DNR, AWB, ROI, Mirror Function, Privacy Mask, ROI
Motion detection and UMMD	Supports both functions
Smart Features	Native support of Motion Detect 2.0 and UMD
Audio	Integrated microphone
Audio Compression	G711A / U, AAC
Network interface	Ethernet 10 / 100M BaseT
Remote access	Web Browser, APP
Interoperability	ONVIF, plug&play with Uniview and Hikvision
P2P	Yes
Power	DC 12 V / 9 W max. / IEEE802.3af PoE
Degree of protection	Weatherproof IP67

Material	Metallic
Temp. operation	-20° C ~ +60° C
Dimensions	70 x 67.5 x 169 mm
Weight	600 g