

IP CCTV / Professional IP cameras / EASY-P / Bullet Cameras

EP-IPB130ZA-8-DL

EasyP



Features

- Easy-P with Artificial Intelligence
- Bullet IP camera
- 1/2.8" Progressive Scan CMOS
- 8 Megapixel (3840x2160)
- Motorized varifocal lens 2.7 ~ 13.5 mm
- Minimum illumination 0.03 Lux | 0 Lux with IR
- IR range of 50 m
- White light range 40 m
- DWDR
- Integrated microphone - Full compatibility with Uniview and Hikvision
- Supports UMD and Motion Detect 2.0: advanced motion detection that is triggered only by human and/or vehicle movement
- AI: intrusion detection, motion detection based on human detection. Reduces false alarms
- ONVIF Compatible
- P2P
- Weatherproof IP67
- PoE

Specifications

Brand	EASY-P
Image sensor	1/2.8" Progressive Scan CMOS
Maximum resolution	8 Megapixel (3840x2160)
Minimum illumination	Colour: 0.03 Lux @(F1.6, AGC ON)
Lighting Scope	IR up to 50m White light up to 40 m
Day/Night	Removable mechanical ICR filter
Electronic Shutter	1/3~1/100000 s
Main Stream rate	2592x1944@30fps; 2560x1440@30fps; 1920x1080@30fps; 1280x720@30fps
Extra Stream rate	1280x720@30fps, 720x480@30fps
Compression	H.264 / H.264+ / H.265 / H.265+ / JPEG / AVI / MJPEG
Bitrate	64 Kbps ~ 6 Mbps
Lens	Motorised 2.7~13.5 mm
Viewing Angle (FOV)	H: 103~29°, V: 54~16°, D: 124~33°
Image improvements	WDR, BLC, HLC, 3D-DNR, AWB, ROI, Mirror Function, Privacy Mask, ROI
Motion detection and UMMD	Supports both functions
Smart Features	Native support of Motion Detect 2.0 and UMD
Audio	Integrated microphone
Audio Compression	G711A / U, AAC
Network interface	Ethernet 10 / 100M BaseT
Remote access	Web Browser, APP
Interoperability	ONVIF, plug&play with Uniview and Hikvision
P2P	Yes
Power	DC 12 V / 12 W max. / IEEE802.3af PoE
Degree of protection	Weatherproof IP67

Material	Metallic
Temp. operation	-20° C ~ +60° C
Dimensions	268 x 95 x 88 mm
Weight	600 g