

IP CCTV / Professional IP cameras / EASY-P / Speed Domes

EP-IPSD5318IT-5

EasyP



Features

- Easy-P with Artificial Intelligence
- IP PTZ Dome Camera
- 1/2.8" Progressive Scan CMOS
- 5 Megapixel (2592x1944)
- PTZ lens 5.35~96.3mm- Optical zoom 18X
- Minimum illumination 0.008 Lux | 0 Lux with IR
- IR Range 80 m
- WDR 120 dB
- AI: intrusion detection, motion detection based on human detection. Reduces false alarms
- Integrated microphone
- Integrated speaker
- ONVIF Compatible
- Weatherproof IP66
- PoE
- RJ45

Specifications

Brand	EASY-P
Image sensor	1/2.8" Progressive Scan CMOS
Lens	PTZ 3.35~10.05mm
Optical Zoom	18X
Maximum resolution	5 Megapixel (2592*1944)
Minimum illumination	Colour: 0.008 Lux @(F1.6, AGC ON)
IR range	80 m
Main Stream rate	5MP(2592*1944)@20fps; 4MP(2560*1440)@25fps; 1080P(1920*1080)@30fps; 720P(1280*720)@30fps
Extra Stream rate	D1(720*480)@20fps; CIF(352*288)@20fps
Compression	H.264 / H.264+ / H.265 / H.265+
WDR	120dB
Image improvements	BLC, AWB, ROI, ROI, Privacy Mask, ROI
Motion detection and UMMD	Supports both functions
Smart Features	Native support of Motion Detect 2.0 and UMD
Audio	Built-in microphone and speaker
Audio Compression	G711A, C711U
Network interface	Ethernet 10 / 100M BaseT
Remote access	Web Browser, APP
Interoperability	ONVIF, plug&play with Uniview and Hikvision (check firmware)
Power	DC 12 V / 12 W max. / IEEE802.3af PoE
Degree of protection	Weatherproof IP66
Temp. operation	-20°C ~ +45°C
Dimensions	230 (h) mm - 136 ? mm.
Weight	1.56 kg