

Model:
VDA-85A5

Index:
A53A185



Description:

VDA-85A5 outdoor station with proximity card function, vandal-proof, surface-mounted, operating in the 2-wire Eura 2 Easy system. Characteristics:

- 4-room apartment,
- surface mounting,
- entry function using a proximity reader,
- made of zinc alloy - resistant to weather conditions,
- color fisheye camera with 1/2.7" CMOS sensor and 170° viewing angle,
- night vision - white light (3 diodes) with a twilight sensor,
- programmable functions (card holder backlight, deadbolt),
- protective canopy included.

Technical specifications:

External cassette

Power supply voltage	24V DC
Video signal parameters	1Vp-p 75 Ohm CCIR
Number of cables required	2, non-polarized
Number of premises served	4
Latch release supply voltage	12VDC, 280mA
Power consumption - standby / operation	0.8W / 3W
Image resolution	500 TVL
Horizontal camera viewing angle	170°
Camera sensor type	Color CMOS 1/2.7" Fisheye
Bolt activation time	1 ~ 99 sec
Housing material	Zinc alloy
Number of relay outputs	1
External cassette installation method	Surface mounted
Adjusting the camera eye position	NO
Night lighting	3 LEDs (white light), with twilight sensor
Proximity reader	Yes
Encryptor	NO
Fingerprint reader	NO
Protective roof	Yes
Protection factor	IP54
Temperature range of the cartridge	- 18°C ~ +55°C
External cassette dimensions (H x W x D)	176x90x27mm
Net weight of the cassette	620g
Package dimensions (H x W x D)	200x104x59mm
Gross weight of package	760g
Package type	Cardboard