

Model:

VDA-95A5

Index:

A53A195



## Description:

Modular multi-family external cassette, fully compatible with the Eura 2 Easy system, made of stainless steel, intended for flush mounting. The basic part of each set of modules used to transmit a video signal is a color camera, whose observation after dark is supported by a set of 3 LED diodes shining with white light. Additionally, the cassette has been equipped with a tenant list with four buttons on the right side. Among the available modules that the cassette can consist of, the following should be mentioned:

- 3.5" colour TFT LCD display, which significantly facilitates operation and configuration of device settings,
- proximity card reader module, allowing for programming of up to 320 cards, which, when brought close to the reader, allow entry to the premises,

- a touch and backlit keyboard module that significantly speeds up the device configuration, selection of the premises to be called, as well as the ability to enter a password to enter the property.

## Technical specifications:

## External cassette

Power supply voltage	24V DC
Video signal parameters	CCIR
Number of cables required	2, non-polarized
Number of premises served	4 (buttons)
Screen type	----
Menu language	----
Latch release supply voltage	12VDC, 250mA
Power consumption - standby / operation	1W / 5W
Image resolution	520TVL
Screen size	----
Camera viewing angle horizontally/vertically	105°
Camera sensor type	ACS Color
Bolt activation time	1 sec / 5 sec
Housing material	Stainless steel
Number of relay outputs	1
External cassette installation method	Concealed
Adjusting the camera eye position	NO
Night lighting	3 LEDs (white light)
Proximity reader	Expandable
Encryptor	Expandable
Fingerprint reader	----
Protective roof	NO
Protection factor	IP44
Temperature range of the cartridge	- 18°C ~ +55°C
External cassette dimensions (H x W x D)	316x133x48mm
Net weight of the cassette	1090g
Package dimensions (H x W x D)	368x145x77mm
Gross weight of package	1257 g
Package type	Cardboard