

FARADAY®

FD369

FULL COLOR



SPECIFICATION

Model NO.	HI-99AIP3B
Camera SPEC	
Pixels	3.0 Mega Pixel
Image Sensor	GC2083
Main processor	FH8852V200
Effective Pixels	2560*1440P
TV System	PAL/NTSC
Main stream	2560*1440/ 2034*1296/ 1920*1080/ 1280*720
Sub-stream	800*448/ 704*576/ 640*360/ 352*228
Electronic Shutter Time	Auto: PAL 1/1-1/10000Sec; NTSC 1/1-1/10000Sec
Usable Illumination	0.01Lux
S/N Ratio	≥52dB
Video Output	Network
Network	
Ethernet	RJ-45 (10/100M)
Protocol	HTTP, TCP/IP, IPv4, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, IP Search
Protocol optional	ONVIF2.4 / Hikvision
P2P	Support
POE	Support
WIFI	N/A
Video Delay	0.3S (Within the Lan)
Smart Phone	iPhone, iPad, Android, Android Pad
Frames Per Second	3MP@20fps/ 2MP@25fps/ 1MP@25fps
Camera Features	
Day/Night	FULL COLOR / B&W
Compression	H.264/ H.265
Image Config	Saturation/ Brightness/ Contrast/ Sharpness, Mirror, 3D NR , White Balance, BLC, FLK (Flicker Control)
Motion Detection	Support
Privacy Masking	3 Rectangular Zone

DWDR / WDR	DWDR
Recording Mode	NVR/ NAS/ CMS/ Web
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German,Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian
Audio	support/G.711
Lens	
Focus Length	F1.3, 3.6mm
Focus Control	Fixed
Lens Type	Fixed
Night Vision	
Infrared LED	2PCS SMT LED (Warm light)
Infrared Distance	20M
IR Status	Under 10 Lux By CDS
IR Power On	Lens Auto Control
General	
Housing	Metal
Bracket	No
IR Cut Filter	YES
Operation Temperature	-10℃ ~ +50℃ RH95% Max
Storage Temperature	-20℃ ~ +60℃ RH95% Max
Power Source	DC12V±10%, 1000mA
Dimension	89*90mm
Weight	0.4kg