

NETWORK Video recorder NVR



FARADAY®



FD374 NVR-8009A-AI

- Ø New GUI, convenient and easy to use, supports functions, such as automatic addition, cross-network segment addition and other functions.
- Ø The camera can be automatically reconnected after changing IP
- Ø Support power amplifier speakers and 3.5mm audio output interface
- Ø Support audio intercom (with headset two-in-one adapter)
- Ø Support VGA, HDMI display simultaneously; HDMI maximum support 2K
- Ø Support HDMI audio output;
- Ø Support APP push alarm function
- Ø Support cloud updating function;
- Ø Support human detection, face detection and vehicle detection function; (need camera support)
- Ø Support alarm linkage, local voice broadcasting and other functions, and support intelligent playback of human detection, face detection and car detection;
- Ø Can connect 9ch 5MP cameras, POE 8CH; 4K Upscale;
- Ø Support ONVIF protocol
- Ø Support GB28181 protocol to facilitate platform access
- Ø Support network and USB backup function, and the backup can be accurate to seconds
- Ø Can control IPC image parameters setting.
- Ø Support remote monitor and playback via EasyVMS & HIVEVIDEO VMS
- Ø APP P6slite can be used for remote monitoring and playback of video;
- Ø You can use APP p6site to scan the code and log in locally

Model: NVR-8009A-AI (1HDD)

APP	 	Neutral APP: HIPLUS Band APP: HIVIDEO
System		
Model	NVR-8009A-AI	
Operation system	Embedded Linux operating system	
Interface		
Operation interface	graphical operation interface, support mouse operation	
Image display	1/4/6/9 screen	

Video	
Video access	9ch 5MP, Support dual stream
Video frame	30fps
Video output	VGA*1, HDMI*1
Image decoding	H.264/H.265
PTZ control	Control the front-end camera with PTZ equipment through the network
Playback channels	1CH 5MP / 4CH 2MP / 4/9CH D1 playback
Record modes	Timing record, motion detection record, manually record, intelligent record
Record query	Time playback, browsing playback, intelligent playback, event retrieval
Intelligent function	
Motion detection	Support (Need camera support)
AI alarm	Support human detection + face detection + Vehicle detection function, linkage push, big screen and voice broadcasting alarm functions
AI playback	Support AI human playback, face playback and vehicle playback function, playback is more accurate.
Audio	
Voice alarm	supports local audio warning broadcast linkage, built-in a variety of warning voice
Voice format	G.711U G.711A G.726
Audio intercom	Support
Audio input	1:1 network audio input according to the number of channels
Audio output	Support HDMI audio output, 3.5mm audio output, 1.25pin connect with loudspeaker sound output
Storage backup	
Video storage	Local hard disk, network(EasyVMS remote recording)
Backup type	Network backup, U-disk
Remote monitoring	
Mobile monitoring	HIVIDEO / HIPLUS
PC monitoring	Support VMS on LAN or WAN remote monitoring
Protocol	Support TCP/IP,IPv4,DHCP,NTP,RTSP,ONVIF,P2P,GB28181, etc
Outer interface	
Video output	1x VGA, 1x HDMI
Network interface	1pcs RJ45 10/100M, self-adaptive ethernet interface
USB	2pcs USB 2.0 interface
Hard disk	1x SATA HDD; SATA interface maximum support 8Tb