

DS-KV6133-WME1 IP Villa door station





- 2 MP camera with IR supplement
- One button calling design for easier calls
- Built-in card reader module
- Standard PoE power supply
- IP65 protection level with aluminum alloy casing
- Call directly to Hik-Connect APP without indoor station



Specification

System parameters		
Operation system	Linux	
ROM	32 MB	
RAM	256 MB	
Processor	Embedded high performance processor	
Display parameters		
Screen size	/	
Operation method	/	
Туре	/	
Resolution	/	
Video parameters		
Lens	1	
Resolution	Main stream: 1920 × 1080p , 1280 × 720p Sub stream: 1280 × 720p , 640 × 480p	
FOV	Horizontal:129°, Vertical: 75°	
Wide dynamic range (WDR)	Support 120 dB	
Supplement light	IR light, up to 2.5 m	
Video compression standard	H.264	
Audio parameters		
Audio input	1 built-in omnidirectional microphone	
Audio compression standard	G722.1、OPUS、G711U、G711A、G726 、AAC_LC、 AAC_LD	
Audio output	1 built-in loudspeaker	
Audio compression bitrate	16/32/64 Kps	
Audio quality	Noise suppression and echo cancellation	
Volume adjustment	Adjustable	
Capacity		
User capacity	2000	
Face capacity	/	
Card capacity	10000	
Network parameters		
Network protocol	TCP/IP, RSTP	
Wi-Fi	2.4GHz, IEEE802.11b, IEEE802.11g, IEEE802.11n	
Bluetooth	/	
3G/4G	/	
Device interfaces		
Alarm input	4	
Network interface	1 RJ-45, 10/100 Mbps self-adaptive	
TAMPER	1	
Exit button	/	
RS-485	1	
USB	/	
Wiegand	/	
TF card	1(Reserved)	




Alarm output	/
Lock control	1 relay, Max. 30 VDC 2 A
Door contact input	1
Audio output	1 external loudspeaker(Reserved)
General	
Button	1 physical button
Installation	Surface mounting, Flush mounting
Indicator	2
Weight	Net weight: 0.190 kg Gross weight: 0.414 kg
Protective level	IP65
Working temperature	-40 °C to 53 °C (-40 °F to 127.4 °F)
Working humidity	10% to 95% (no-condensing)
Dimension (W × H × D)	181.6 mm × 103.6 mm × 29.5 mm (7.1" × 4.0" × 1.1")
Battery	/
Application environment	Outdoor
Power consumption	< 10 W
Language	English, Arabic, French (Europe), Russian, Spanish (Europe), Italian, German, Polish, Turkish, Portuguese, Portuguese (Brazil), Uzbek, Kazakh, Czech, Hungarian, Dutch, Romanian, Bulgarian, Ukrainian, Croatian, Serbian, Greek, Lithuanian, Estonian, Latvian, Norwegian, Danish, Slovenian, Slovak, Hebrew, Swedish, Finnish, Mongolian, Vietnamese, Traditional Chinese

Available Model

DS-KV6133-WME1

Dimension



Unit:mm [inch]



Headquarters No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 www.hikvision.com

Follow us on social media to get the latest product and solution information.





HikvisionHQ



HikvisionHQ



Hikvision Corporate Channel



6 hikvisionhq