

UV-XVR-104G3

Video recorder 5n1

Uniarch

4 CH HDTVI / HDCVI / AHD / CVBS

+ 2 extra IP

Audio

Supports 1 hard disk



Uniarch

DVR 5n1

4 BNC video CH (IP-replaceable)

AHD, TVI, CVI, CVBS, CVBS

48 Mbps bandwidth supported

Maximum IP resolution 4 Mpx

Maximum analog resolution 5 Mpx

Audio

HDMI and VGA output

RS485

2 x USB 2.0

Mouse

Space for 1 HDD up to 8 TB

WEB, CMS, Smartphone and NVR interface

ONVIF Compatible

Specifications

Brand	Uniarch
Video format	HDTVI / HDCVI / AHD / CVBS / IP
Video inputs	4CH BNC
Hybrid configuration	Up to 6 IP Channels (4Mpx) replacing all the BNC channels
Video outputs	1 HDMI Full HD, 1 VGA
Audio inputs	1 Channel RCA
Audio outputs	1 Channel RCA
Bidirectional audio	Reusing the audio input/output
Display resolution	1920x1080@60Hz, 1920x1080@50Hz, 1600x1200@60Hz, 1280x1024@60Hz, 1280x720@60Hz, 1024x768@60Hz
Maximum IP recording resolution	4 Mpx
Analog cameras supported	TVI / AHD: 5MP@20fps, 4MP@30fps,1080P@30fps, 720P@60fps
	CVI: 5MP@20fps, 4MP@30fps, 1080P@30fps, 720P@30fps
Main Stream recording encoding	5MPLite@12fps; 4MPLite@15fps; 1080P@15FPS; 720P@25FPS
Extra Stream recording encoding	D1@12FPS; D1@15FPS; D1@25FPS
Recording method	Manual, programmed, motion detection
Internal memory	1 HDD SATA 3.5" of up to 8TB (not included)
External interface	2 x USB (Mouse and backup) / RJ45 10M/100M/1000M (Ethernet) / RS485
Remote access	Web Browser, CMS Software (EZStation), Smartphone (EZView/EZLive)
Power	DC 12V / 8W
Dimensions / Weight	260mm × 218mm × 47mm / 1.1 kg

SF-T010-2B1L

Safire Smart

Turret camera 4 in 1 Range B1

2 Mpx (1920x1080) , 1/3" CMOS

lens 2.8 | IR range 20 m

DWDR, HLC, BLC, AGC

Weatherproof IP67



Safire Smart

Range B1 Economical

Turret HDTVI, HDCVI, AHD and Analog Camera
CMOS 1/3"

2Mpx (1920x1080)

Output 4in1

2.8mm lens

0 Lux

IR Range 20 m

DNR

IR Cut

Mirror

HLC, BLC, AGC, DWDR

Weatherproof IP67

Specifications

Brand	Safire Smart
Range	B1 Economic
Image sensor	1/3" CMOS
Maximum resolution	2 Mpx (1920x1080)
Resolution	2Mpx (25fps)
Lens	2.8 mm
Minimum illumination	0.01 Lux @(F1.2, AGC ON)
Infrared lighting	0 Lux / IR range up to 20 m (ICR)
Day / Night	Auto / Colour / BW (Black and White)
Video output	1 x BNC switchable between HDTVI / HDCVI / AHD / CVBS
Video output switching	Via Switch
Basic functions	OSD menu (remote)
Configurable OSD functions	DWDR, DNR, AWB, ATW, BLC, AGC, Mirror, Smart IR
Lens Adjustment	3 Axis
Power	DC 12 V / 250 mA, 3W max
Degree of protection	Weatherproof IP67
Temp. operation	-30° C ~ +50° C
Material	Metal body and plastic bracket
Dimensions	82.8 (H) x 94.6 (Ø) mm
Weight	250 g