

SF-SD6025IW-F4N1

4N1 1080p Motorised Camera
1/2.8" Progressive Scan CMOS
Average speed 80°/segundo
25X Optical Zoom (4.8~120 mm
Lens) Auto Iris
WDR / IR LEDs 100m
Suitable for exterior



Safire
Motorised dome camera HDTVI, HDCVI, AHD & Analogue
Average speed 80°/segundo
25X Optical zoom
16X Digital zoom
1/2.8" 2 Megapixel CMOS
HD 1080P (1920x1080)
Output 4in1
4.8~120 mm Varifocal lens
0 Lux
LED Range 100 m
3DNR
IR Cut
WDR
Pelco P/D protocols supported
OSD Menu
Weatherproof IP66

Specifications

Brand	SAFIRE
Image sensor	1/2.8" Progressive Scan CMOS
Resolution	1080p (1920x1080) at 25 FPS
Video output	1x BNC format HDTV//HDCVI//AHD/CVBS
Minimum illumination	0.005 Lux (colour) / 0.001 Lux (B/N)
Infrared lighting	Automatic IR LED's, range 100 metres
Lens	Varifocal 4.8~120.0 mm (Optical Zoom 25X)
Digital zoom	16X
Electronic shutter	1/1s~1/10,000s
Day / Night	Removable mechanical ICR filter
Noise reduction	3D-NR
Gain Control	Auto / Manual
Backlight compensation	BLC / WDR
White balance	Auto, ATW, Interior, Exterior, Manual
Privacy masks	Up to 8 areas
Pan/Tilt Range	Horizontal: 0°~360°, Vertical: -15°~90° auto flip 180°
Manual speed	Horizontal: 0.1°~80° /s, Vertical: 0.1° ~80°/s
Speed between Presets	Horizontal: 80° /s, Vertical: 80° /s
Preset positions	256 preset, 5 auto pattern, 10 auto tour, auto pan, auto scan
Communication	RS485, Pelco P / Pelco D / SAFIRE
Audio	No
Alarms	No
Power	DC 12 V / 2 A
Temp. operation	-30° C ~ +65° C
Degree of protection	IP66 / Surges 4000V
Dimensions (without bracket)	295 mm (H) x 165 (Ø) mm
Weight (without bracket)	2000 g