

CCTV / HD 4n1 / Cameras

SF-T940-WIDE-5P4N1

High Resolution 4N1 Camera

High Resolution PRO Series

The higher resolution of 5Mpx provides a significant improvement in the level of detail when identifying the events collected in the recordings. Good sharpness and definition during the day and high performance at night, highlighting its sensitivity of 0.01Lux and its Smart Matrix IR LEDs with improved coverage and automatic adjustment.

- 5 Megapíxel Resolution
- High Performance CMOS Sensor
- 110° Wide Angle Lens without deformation
- Smart IR Up to 20 m
- Digital WDR | 2D DNR
- IP67 Weatherproof



Technical Specification

Sensor de imagen	5 MP CMOS image sensor
Max. Resolución	2560 (H) × 1944 (V)
Iluminación mínima	Color: 0.01 Lux @ (F1.2, AGC ON), 0 Lux with IR
Tiempo de obturación	PAL: 1/25 s to 1/50, 000 s,NTSC: 1/30 s to 1/50, 000 s
Día y Noche	IR cut filter
Ajuste de ángulo	Pan: 0° to 360°; Tilt: 0° to 75°; Rotate: 0° to 360°
Lente	2.4 mm fixed Lens
Focal Length & FOV	110°
Montura del lente	M12
Configuración de imagen	Brightness, Sharpness, DNR, Mirror, Smart IR
Frame Rate	PAL: 5 MP@20fps, 4 MP@25fps, 1080p@25fps,NTSC: 5 MP@20fps, 4 MP@30fps, 1080p@30fps
Modo día/noche	Auto/Color/BW (Black and White)
Wide Dynamic Range (WDR)	DWDR
Mejora de la imagen	BLC
Balance de blancos	ATW/MWB
AGC	Support
Salida de Vídeo	Switchable TVI/AHD/CVI/CVBS
Material	Metal
Dimensión	91 mm × 82.6 mm × 68.3 mm (3.58" × 3.25" × 2.69") Approx. 350 g (0.77 lb.)
Operating Condition	-40 °C to 60 °C (-40 °F to 140 °F), humidity: 90% or less (non-condensation)
Comunicación	Up the coax, Protocol: Safire-C (TVI output)
Idioma	English
Fuente de alimentación	12 VDC ±25%
Consumo	Max. 4.3 W
Rango IR	Up to 20 m
Protección	IP67