

CCTV / HD 4n1 / Cameras

SF-T942SW-2P4N1

Starlight IR Solution 4N1 Camera

Starlight PRO Series

High sensitivity Starlight 0.005Lux sensors, to obtain a great performance in low light situations that use IR illumination. The solution is powered by 3DNR noise reduction and a Sense-Up slow-speed shutter. Wide dynamic range (WDR) of 120 dB solves any situation of backlight or high light contrast.

- 1080p Resolution
- Starlight CMOS Sensor
- 2.8 mm Fixed Lens
- Smart IR Up to 30 m
- WDR | 3D DNR Advanced funtions
- IP67 Weatherproof



Technical Specification

Image Sensor	2.0 megapixel progressive scan CMOS
Max. Resolution	1920 (H) ×1080 (V)
Min. Illumination	0.005 Lux@(F1.2, AGC ON), 0 Lux with IR
Shutter Time	PAL: 1/25 s to 1/50, 000 s,NTSC: 1/30 s to 1/50, 000 s
Day & Night	IR cut filter
Angle Adjustment	Pan: 0° to 360°, Tilt: 0° to 75°, Rotation: 0° to 360°
Signal System	PAL/NTSC
Lens Type	2.8 mm
Focal Length & FOV	106°
Lens Mount	M12
Image Parameters Switch	STD/HIGH-SAT
Image Settings	Brightness, Sharpness, 3D DNR, Mirror, Smart IR
Frame Rate	PAL: 1080p@25fps,NTSC: 1080p@30fps
Day/Night Mode	Auto/Color/BW (Black and White)
Wide Dynamic Range (WDR)	≥ 120 dB
Image Enhancement	BLC, HLC
Noise Reduction	Level 1 to 9
AGC	High/Medium/Low
Video Output	Switchable TVI/AHD/CVI/CVBS
Material	Metal
Dimension	89.47 mm × 68.2 mm (3.52" × 2.68") Approx. 240 g (0.53 lb.)
Operating Condition	-40 °C to 60 °C (-40 °F to 140 °F), Humidity: 90% or less (non-condensation)
Language	English
Power Supply	12 VDC ±25%, *You are recommended to use one power adapter to supply the power for one camera.
Consumption	Max. 4.6 W
IR Range	Up to 30 m
Protection	IP67