

SF-XVR6104MS

Safire 5n1 H.265Pro+ Recorder
Audio over coaxial cable
4CH HDTV/HD/HD/HD/ 4+2
IP
4Mpx Lite/1080p (12FPS)
Full HD HDMI and VGA Output
1 CH audio / 1 HDD



Safire
DVR 5n1
4 CH video HDTV/HD/HD/HD / 4+2 IP / 1 CH audio
H.265Pro+/H.265Pro/H.264+/H.264
Resolution 4Mpx Lite /1080p (15FPS) or 1080PLite/720P (25FPS)
PTZ Control (RS485/Coaxial)
Audio over coaxial cable
No alarms
HDMI Full HD, VGA & CVBS Outputs
Mouse
Space for 1 HDD
Cloud storage for substream (OneDrive, Dropbox...)

Specifications

Brand	SAFIRE
Video format	HDTVI / HDCVI / AHD / CVBS / IP
Video inputs	4 Channels BNC, (HDTVI / HDCVI / AHD / CVBS)
Hybrid configuration	Default: 4 Channels from BNC and 4 (substitution) + 1 (extra) IP Channels (up to 6Mpx) Enhanced IP Mode:4 Channels from BNC and 4 (substitution) + 2 (extra) IP Channels (up to 6Mpx) Enhanced IP mode limits bandwidth to 4Mbps per IP channel Note: Enhanced IP mode is not compatible with Enhanced VCA mode
Input bandwidth	24 Mbps
Video outputs	1 HDMI Full HD, 1 VGA
Audio inputs	1 Channel RCA
Audio outputs	1 Channel RCA
Bidirectional audio	Reusing the audio input/output
Video / audio compression	H.265Pro+ / H.265Pro / H.264+ / H.264 / G.711u
Display resolution	1920x1080, 1280x1024, 1280x720, 1024x768
BNC input resolution	4Mpx / 3Mpx / 1080p / 720p
Main Stream coding	4Mpx Lite/ 3Mpx (CH1) / 1080p (15 FPS), 1080p Lite 720p/ / VGA / WD1 4CIF/ CIF (25FPS)
Extra Stream coding	WD1 / 4CIF (12FPS) / CIF (25 FPS)
Simultaneous multifunction	Pentaplex: Live, Recording, Playback, Backup and Remote Access
Alarms	No
Video analysis	Default: 2 CH VCA, Enhanced VCA Mode: 4 CH VCA Tripwire Area intrusion Audio exception
Recording method	Manual, programmed, motion detection, alarm
Backup	USB / Network / Cloud (Microsoft One Drive, Dropbox)
Internal memory	1 HDD SATA 3.5" of up to 10TB (not included)
Communication	RS485 (PTZ) / 2 x USB 2.0 (Mouse and Backup) / RJ45 (Ethernet)
Remote access	Web browser, Smartphone App and Safire Control Center CMS Software
Power	DC 12 V / 1.5 A (Consumption without HDD < 6 W)
Dimensions / Weight	45 (H) x 200 (W) x 200 (D) mm / 1 Kg