

CCTV / HD 4n1 / Cameras

SF-B023A-5P4N1-0600

High Resolution 4N1 Camera with Audio

High Resolution PRO Series | Audio Solution

The higher resolution of 5Mpx provides a significant improvement in the level of detail when identifying the events collected in the recordings. Good sharpness and definition during the day and high performance at night, highlighting its sensitivity of 0.01Lux and its Smart Matrix IR LEDs with improved coverage and automatic adjustment. Integrated microphone that transmits audio over the coaxial cable itself.

- 5 Megapíxel Resolution
- High Performance CMOS Sensor
- 6 mm Fixed Lens
- Smart IR Up to 40 m
- Built-in Mic Audio over Coaxial
- Digital DWDR | 2D DNR
- IP67 Weatherproof



Technical Specification

Sensor de imagen	5 MP CMOS
Señal del sistema	PAL/NTSC
Resolución	2560 (H) × 1944 (V)
Frame Rate	TVI: 5 MP @ 20 fps, 4 MP @ 30 fps, 4 MP @ 25 fps, 1080p @ 30 fps, 1080p @ 25 fps AHD: 5 MP @ 20 fps, 4 MP @ 30 fps, 4 MP @ 25 fps CVI: 4 MP @ 30 fps, 4 MP @ 25 fps CVBS: PAL/NTSC
Iluminación mínima	0.01 Lux @ (F1.2, AGC ON), 0 Lux with IR
Tiempo de obturación	PAL: 1/25 s to 1/50,000 s; NTSC: 1/30 s to 1/50,000 s
Lente	2.8 mm, 3.6 mm, 6 mm fixed focal lens
Campo de visión	2.8 mm, horizontal FOV: 85°, vertical FOV: 63°, diagonal FOV: 110° 3.6 mm, horizontal FOV: 80°, vertical FOV: 63°, diagonal FOV: 105° 6 mm, horizontal FOV: 57°, vertical FOV: 43°, diagonal FOV: 72°
Montura del lente	M12
Día y Noche	IR Cut Filter
WDR (amplio rango dinámico)	Digital WDR
Ajuste de ángulo	Pan: 0° to 360°, Tilt: 0° to 180°, Rotation: 0° to 360°
Modo de imagen	STD/HIGH-SAT
AGC	Yes
Modo día/noche	Auto/Color/BW (Black and White)
Balance de blancos	Auto/Manual
Modo AE (exposición automática)	BLC; HLC; Global; DWDR
Reducción de ruido	2D DNR
Idioma	English
Función	Sharpness; Mirror; Brightness; Smart IR
Salida de Vídeo	Switchable TVI/AHD/CVI/CVBS
Entrada de audio	Built-in mic
Condiciones de operación	-40°C to 60°C (-40°F to 140°F), Humidity: 90% or less (non-condensing)
Fuente de alimentación	12 VDC ± 25%
Consumo	Max. 4.5 W
Nivel de protección	IP67
Material	Front cover: Metal, Main body: Plastic
Rango IR	Up to 40 m
Comunicación	Safire-C

Dimensión	78.9 mm × 75.4 mm × 216.6 mm (3.10" × 2.97" × 8.53")
	Approx. 338 g (0.75 lb.)