

Video-intercoms / Outdoors Station

## SF-VIMOD-CAM-2

### Outdoor station

#### Modular Outdoor Station

The line up of modular video intercoms is aimed at all types of environments, villas or apartments. Aesthetic and compact design, suitable for all types of installations thanks to its IP or 2-wire communication modes. 2MP camera with perfect visualization of the entire environment thanks to its 180° image angle, it also stands out for its night image. Second door activation function for users who need it. With different functionalities that every type client wants such as two-way audio, remote access from the app and remote door unlocking. It has a possible add-ons of different modules to make it more complete such as unlocking by cards or password or calling the different apartments.

- Modular Videointercom 2 wire
- Communication 2 wire to IP
- Bidirectional Audio
- 2 relay for doors
- 2 Mpx Camera with Viewing angle 180°
- Mobile App
- Flush Mounting
- Outdoor Installation



## Technical Specification

Operation method	Physical button
Supplement light	IR supplement
Lens	1
FOV	Horizontal 180°, vertical 96°
Pixel	Main stream: 1920 × 1080, (720p configurable); sub stream: 720 × 480
Audio quality	Noise suppression and echo cancellation
Sub door station capacity	16
Communication protocol	TCP/IP, RTSP
Wired network	Two-wire transmission
Exit button	2
Lock control	2
Door contact input	2
Power interface	1
Button	1
Installation	Wall mounting
Protective level	IP65
Power supply method	24 VDC two-wire power supply (< 16 W) or 12 VDC independent power supply (< 20 W)
Working temperature	-40 °C to 60 °C (-40 °F to 140 °F)
Working humidity	10% to 95%
Dimensions	98 mm × 99.8 mm × 43.9 mm (3.86" × 3.93" × 1.73")
Application environment	Outdoor
Power consumption	24 VDC two-wire power supply (≤16 W) or 12 VDC independent power supply 20 W)
Platform	Safire Connect & Safire Control Center