

SF-VI105E-IP

Video intercom IP

2Mp camera with pinhole lens

Bidirectional audio

Mobile App for remote monitoring

Anti-vandalism zinc alloy IK09

Surface Mount : PoE Standard



Safire

IP video-intercom with 2Mpx camera

Adjustable wide angle lens

Integrated speaker and microphone

IR night vision

TCP/IP and RS485 connection

PoE IEEE802.3af

Remote monitoring through Safire Control Center-software, mobile app or interior monitor

Remote door opening

Surface mounting

Anti-vandalism stainless steel surface IK09

Specifications

Brand	Safire
Operating system	LINUX OS
Image sensor	2Mpx with WDR
Lens	3.47mm Pinhole
Viewing angle	H: 88° D: 45° (Device rotates between -50° ~+50° manually when installing)
Infrared light	IR with range up to 5 meters
Audio	Bidirectional audio with microphone and speaker
Keypad	Mechanical call button
Relay	1 for lock control.
Inputs	Exit button, feedback, door sensor, tamper
Remote access	Web browser, phone app or Safire Control Center-software
Events	Motion detection and image captures
Network interface	Ethernet 10/100 BaseT
Power	DC 12 V / 850 mA max. / estándarIEEE802.3af PoE
Degree of protection	IP66, anti-vandalic IK09
Material	Zinc alloy
Temp. operation	-30° C ~ +50° C
Dimensions	161.9 (H) x 74.1 (W) x 53.2 (D) mm
Weight	773 g