

SF-IPT010A-2B1

Safire Smart

Turret IP camera range B1

Resolution 2 Megapixel (1920x1080)

Lens 2.8 mm | Built-in microphone

IR range 20 m | PoE (IEEE802.3af) m

Waterproof IP67



Safire Smart

B1

Turret IP Camera

1/3" Progressive Scan CMOS

2 Megapixel (1920x1080)

2.8 mm Lens

0 Lux

IR Range 20 m

Compression H.265+ / H.264+

DWDR

3DNR

Integrated microphone

WEB, CMS, Smartphone and NVR interface

ONVIF Compatible

PoE (IEEE802.3af)

Weatherproof IP67

Specifications

Brand	Safire Smart
Range	B1
Image sensor	1/3" Progressive Scan CMOS
Maximum resolution	2 Megapixel (1920x1080)
Minimum illumination	Colour: 0.0462 Lux @(F1.6, AGC ON), 0 Lux with IR
IR range	20 m
Day/Night	Removable mechanical ICR filter
Electronic Shutter	1/3~1/100.000 s
Main Stream rate	25 FPS (1080P, 720P)
Extra Stream rate	25 FPS (D1, VGA, CIF, 480x240)
Third Stream Rate	25 FPS (D1, 480x240, CIF)
Compression	H.265+, H.265, H.264+, H.264
Bitrate	64 Kbps – 8 Mbps
Lens	2.8 mm
Viewing Angle (FOV)	H: 87°, V: 48°, D: 103°
Range performance	49 m (D), 19 m (O), 8 m (R), 5 m (I)
Image improvements	DWDR, BLC, HLC, 3D-DNR, AWB, ROI, ROI, Mirror function, Privacy masking, ROI
Motion Detection	Yes
Smart Features	Area intrusion, Line crossing, abandoned object, removed object, Video exceptions (change of scene, video loss, ...)
Audio	Integrated microphone
Audio Compression	G711A / U
Network interface	Ethernet 10 / 100M BaseT
Remote access	Web Browser, Smartphone App Safire Smart, PC Software Safire Smart VMS
Interoperability	ONVIF
Power	DC 12 V / 375 mA / 4.5 W max. / IEEE802.3af PoE
Degree of protection	Weatherproof IP67
Material	Plastic
Temp. operation	-20° C ~ +55° C
Dimensions	94.8 (ø) x 82.8 (H) mm
Weight	287 g