

IP CCTV / Professional IP cameras / Safire Smart / Bullet Cameras

SF-IPB080A-6B1-DL

SAFIRE SMART



Features

- Safire Smart
- Range B1 with dual light
- Bullet IP camera
- 1/2.7" Progressive Scan CMOS
- 6 Megapixel (3200×1800)
- 2.8 mm Lens
- 0 Lux
- DualLight range 20 m
- Compression H.265+ / H.265 / H.264+ / H.264
- WDR
- 3DNR
- Integrated microphone
- WEB, CMS, Smartphone and NVR interface
- ONVIF Compatible
- PoE (IEEE802.3af)
- Weatherproof IP67

Specifications

Brand	Safire Smart
Range	B1 with dual light
Image sensor	1/2.7" Progressive Scan CMOS
Maximum resolution	6 Megapixel (3200×1800)
Minimum illumination	Colour: 0.008 Lux @(F1.6, AGC ON), 0 Lux with IR
Dual Light	IR and White Light Range: 20 m
Day/Night	Removable mechanical ICR filter
Electronic Shutter	1/2~1/100.000 s
Main Stream rate	20 FPS (6Mpx) 30 FPS (4Mpx, 1080P)
Extra Stream rate	30 FPS (720P, D1, CIF, 480×240)
Compression	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Bitrate	64 Kbps ~ 8 Mbps
Lens	2.8 mm
Field Of View (FOV)	H: 110.5°, V: 57°, D: 131°
Range performance	60 m (D), 24 m (O), 12 m (R), 6 m (I)
Image improvements	WDR, BLC, HLC, 3D-DNR, AWB, ROI, Mirror Function, Privacy Mask, ROI
Motion Detection	Yes
Audio	Integrated microphone
Audio Compression	G711A / U
Network interface	Ethernet 10 / 100M BaseT
Internal memory	MicroSD card up to 256GB
Remote access	Web Browser, Smartphone App Safire Smart, PC Software Safire Smart VMS
Interoperability	ONVIF
Power	DC 12 V / 6 W max. / IEEE802.3af PoE



Degree of protection	Weatherproof IP67
Material	Metal and plastic
Temp. operation	-30° C ~ +60° C
Dimensions	75 (H) x 75 (W) x 167.6 (D) mm
Weight	382 g