

Networking / Switches / Unmanaged

SF-SW1916HIPOE-HF-300

SAFIRE



Features

- Desktop Switch
- 14 PoE+ ports 30W 802.3af/at RJ45 10/100 Mbps
- 1 Hi-PoE port 60W 802.3af/at/bt RJ45 10/100
- 1 Hi-PoE port 60W 802.3af/at/bt RJ45 10/100/1000
- 2 Uplink ports RJ45 10/100/1000Mbps
- PoE Extended up to 250m
- 1 Uplink SFP Port 10/100/1000Mbps
- Supports PoE power supply up to 300W in total for all ports
- AI Watchdog

Specifications

Interfaces	PoE Ports 1~16 Uplink Ports 1~2 10/100/1000Mbps Uplink SFP port 10/100/1000Mbps
Ports Speed	15x 10/100Mbps + 3x 10/100/1000Mbps + 1x 10/100/1000Mbps
PoE features	Up to 300W in total for all ports 1~14 PoE+ Ports Up to 30W 802.3af/at 10/100Mbps Port 15 Hi-PoE Up to 60W 802.3af/at/bt 10/100Mbps Port 16 Hi-PoE Up to 60W 802.3af/at/bt 10/100/1000Mbps
Transmission distance	130 meters
Bandwidth	12,8Gbps
MAC Table	8K
Latency	10 to 100Mbps <16?s (utilizando 64 byte de tamaño de paquete)
AI PoE	PoE Watchdog Puertos 1~24 - Reinicio automático de la alimentación de un puerto PoE cuando se detecta un posible fallo. PoE Extendido Hasta 250m de cableado
Alimentación	Toma Trasera 90~240V
Protecciones	6KV contra Rayos 8KV Protección ESD
Instalación	Escritorio y enrackable
Temperatura de funcionamiento	-30° C ~ 60° C
Dimensiones	430 x 180 x 45 mm
Peso	2,65Kg