

Access Controls / Readers

# SF-AC1104MF-WR

## Access Reader for controller

### Access Reader

High speed biometric and RFID card readers thanks to wiegand and RS485 communication. Identification by Mifare cards, fingerprint or keypad combined with an easy installation and a great durability, which consolidate the characteristics of the devices they support.

- Access Reader for controller
- Mifare Card Identification
- RS485 Communication
- Wiegand 26/34
- Outdoor Installation
- Antivandal



## Technical Specification

Power Supply	12V DC
Working Temperature	-20°C to + 65°C (-4°F to + 149°F)
Working Humidity	10% to 90% (Non Condensing)
Working Current	≤500mA
Reading Frequency	13.56MHz
Reading Range	≤50mm (≤1.97")
ID Settings	via DIP Switch
Audio Alert	Beeper
Power Consumption	≤2W
Keypad	No Keypad
Certifications	FCC, CE
LED Indicator	Power Indicator; Status LED Indicator
Protection Level	IP 65
Dimensions	118 mm × 76 mm × 23 mm (4.65" × 2.99" × 0.91")
	≤ 0.52kg
Installing Method	Applied for 86 & 120 Gang Box
Processor	32-bit
Communication Interface	RS485/Wiegand (Set via DIP Switch)