

SF-IPPT400A-2US-DL

IP Camera PT 2 Mpx Ultra Low Light
X
1/2.7" Progressive Scan CMOS
Fixed lens 2.8 mm | PAN & TILT
Dual Light
Built-in microphone and speaker



Safire
IP Camera PT- ULTRA Range
1/2.7" Progressive Scan CMOS Ultra Low Light X
2 Megapixel (1920x1080)
2.8 mm Lens
Compression H.265/H.264
IR Cut
0 Lux
White back-up light up to 30 m
Built-in speaker
RJ-45 10/100M BaseT
WEB, CMS, Smartphone and NVR interface
ONVIF Compatible
Micro SD card recording
PoE IEEE802.3af
Weatherproof IP66

Specifications

Brand	SAFIRE
Image sensor	1/1.8" Progressive Scan CMOS Night Colour
Maximum resolution	2 Megapixel (1920×1080)
Minimum illumination	Color: 0.01 Lux @(F1.2, AGC ON), B/W: 0 Lux with IR
Lighting	White light Range 30m IR light Range 30m
Main Stream coding	(1920 × 1080, 1280 × 720) 25 fps
Sub-Stream Encoding	(640 × 480, 640 × 360) 25 fps
Compression	H.265+/ H.265 / H.264+/ H.264
Lens	2.8 mm (H: 105°, V: 57.3°)
Electronic shutter	1/1s~1/30,000s
Manual Speed	Horizontal: 21°/s Vertical: 19°/s
Day / Night	Removable mechanical ICR filter
Image improvements	BLC, HLC, 120dB WDR, 3D-NR, AGC, AWB, MD, Privacy Masking, ROI
Advanced functions	No
FOV	Horizontal: 91.5°, Vertical: 46.5°, Diagonal: 109..
Internal memory	MicroSD card, Max 256 GB
Audio	Microphone and speaker incorporated
PTZ Control	Through network access
Network interface	Ethernet 10 / 100M BaseT
Remote access	Web browser, Safire Control Center Smartphone App and PC Software
Interoperability	ONVIF, PSIA, CGI
Power	DC 12 V, 0.3 A / 10.8W, PoE (802.3af)
Temp. operation	-30° C ~ +40° C
Degree of protection	IP66
Dimensions (without bracket)	182 (H) x 120 (Ø) mm
Weight (without bracket)	700 g