

SF-AC109-WIFI

Standalone access control

Access by EM card, PIN and App

Relay, pushbutton and buzzer outputs

Wiegand 26 and WiFi | Timing control

Tuya Smart App for remote
management and openings

Suitable for exterior IP68



Safire

Standalone access control

Access by EM card, password, mobile application and/or combinations

Metal keyboard and casing

LED indicator

Wiegand 26 and WiFi

Integrated controller (Push button, bell and relay)

Opening and closing time control

Suitable for outdoors IP68 and anti-vandalism

Compatible with the Tuya Smart application for management and opening

Specifications

Brand	Safire
Model	SF-AC109-WIFI
Capacity	Up to 2.000 cards/passwords
Identification modes	Card, PIN, App and combinations
RFID proximity card	EM 125 kHz
Inputs/outputs	NO/NC relay, push button and buzzer
Communication	Wiegand 26 and WiFi
Power	DC 12 V
Consumption in idle mode	? 30 mA
Degree of protection	Suitable for exterior IP68
App	Tuya Smart
Functions through APP	User creation through App (only permission 24h) / Temporary codes / Remote openings
Temp. operation	-40° C ~ +60° C
Dimensions	75 (W) x 110 (H) x 25 (D) mm
Weight	700 g