

SF-SW2624HIPOE-GF-300

Safire Switch Hi-PoE

24 PoE + 2 SFP Uplink ports

Gigabit port speed 10/100/1000Mbps

22 PoE+ Ports 30W + 2 Hi-PoE Ports

60W

PoE Watchdog

Up to 300W Total PoE Power



Desktop Switch

22 PoE+ ports 30W RJ45 10/100/1000 Mbps

2 Hi-PoE+ ports 60W 802.3bt 10/100/1000Mbps + 2 Uplink SFP 10/100/1000Mbps

Supports PoE power supply up to 300W in total for all ports

AI Watchdog

Specifications

Interface	24 PoE + 2 Uplink SFP ports
Port speed RJ45	24x 10/100/1000Mbps + 2x 10/100/1000Mbps
PoE features	Up to 300W in total for all ports Ports 1~22 PoE+ Up to 30W 802.3af/at Port 23~24 Hi-PoE Up to 60W 802.3af/at/bt
Transmission distance	130 meters
Bandwidth	52Gbps
MAC Table	8K
Latency	10 to 100MBps < 16?s (using 64 packet size byte)
AI PoE	PoE Watchdog Ports 1~24 - Automatic restart of the power supply to a PoE port when a possible failure is detected.
Power	Rear Socket 90~240V
Protections	6KV against Rays 8KV ESD Protection
Operating temperature	-30° C - 60° C
Dimensions	18 (D) x 45 (H) x 430 (W) mm
Weight	2,65Kg