

Networking / Switches / Unmanaged

SF-SW0908HIPOE-120

SAFIRE



Features

- Desktop Switch
- 9 mbps ports RJ45 10/100
- 6 PoE+ ports 30W 802.3af/at + 2 Hi-PoE ports 60W 802.3bt
- Supports PoE power supply up to 120W in total for all ports
- AI Watchdog
- Auto PoE Extended up to 250m 10Mbps

Specifications

Interface	8 RJ45 PoE port(s) + 1 Up-link port(s)
Port speed RJ45	8x 10/100Mbps - 1x 10/100Mbps
PoE features	Up to 120W in total for all ports Ports 1~6 PoE+ Up to 30W 802.3af/at Port 7~8 Hi-PoE Up to 60W 802.3af/at/bt
Transmission distance	Auto PoE Extended 250m a10Mbps There is no need to manually configure the Extended PoE function, the switch automatically detects the distance of the cable and the distance of the cable to the switch
Bandwidth	1.8Gbps
MAC Table	2K
Latency	10 to 100MBps < 16?s (using 64 packet size byte)
AI PoE	PoE Watchdog Ports 1~8 - Automatic restart of the power supply to a PoE port when a possible failure is detected.
Power	AC Front Socket 90~240 V
Protections	6KV against Rays 8KV ESD Protection
Operating temperature	-30° C - 60° C
Dimensions	187 (D) x 43 (H) x 139 (W) mm
Weight	1Kg