

Networking / Switches / Unmanaged

SF-SWI1008HIPOE-GF-AC-130-DIN

SAFIRE



Features

- IP40 Industrial Switch
- AC power supply
- 8 PoE ports RJ45 Gigabit 10/100/1000 Mbps
- 6 PoE+ ports 30W 802.3af/at + 2 Hi-PoE ports 60W 802.3bt
- 2 SFP Gigabit ports
- DIN-rail installation
- Supports PoE power supply up to 130W in total for all ports
- AI Watchdog
- Extended temperature range -40°C to 70°C

Specifications

Interfaces	8 PoE ports + 2 SFP
Port speed RJ45	8x RJ45 Gigabit 10/100/1000Mbps + 2 SFP Gigabit 10/100/1000Mbps
PoE features	Up to 130W in total for all ports Ports 1~6 PoE+ Up to 30W 802.3af/at Port 7~8 Hi-PoE Up to 60W 802.3af/at/bt
Transmission distance	130 meters (The use of quality cable is recommended to obtain this distance)
Bandwidth	20Gbps
Reshipment Rate	14,88Mbps
MAC Table	8K
Latency	10 to 100MBps <16?s (utilizando 64 byte de tamaño de paquete)
AI PoE	PoE Watchdog Puertos 1~8 - Reinicio automático de la alimentación de un puerto PoE cuando se detecta un posible fallo.
Alimentación	AC 90~264V DC 48-52V
Protecciones	6KV contra Rayos 8KV Protección ESD IP40
Temperatura de funcionamiento	-40° C - 70° C
Dimensiones	145 x 110 x 88mm
Peso	0,9 Kg