

ZENTO FAMILY

THE ZENTO IS ONE OF OUR MOST POPULAR SECURITY GATES, TRIED AND TRUSTED IN THOUSANDS OF RETAIL OUTLETS IN EUROPE AND AROUND THE GLOBE.

The Zento is an extruded aluminium lightweight yet robust antenna, perfectly matching to your store interior and non-obtrusively fulfilling its task.

Designed with maximum transparency, minimising entrance obstruction yet offers maximum detection of hard tags and disposable tags in challenging store environments.




The Zento is available in **RF** with TX/RX and TRX versions, with PC connection and remote monitoring available for TRXs.



ZENTO FAMILY (DISTANCE DATA BETWEEN ANTENNAS)



	# Product No.	TRx mono	Shield on side	Detection 4x4 paper label (normal/max)	Detection round hardtag (normal/max)
L-Line (Large)					
Zento L-150 RF AFT-TRx	P0200352	yes		2/2,4m 78/94in	2,4/2,8m 78/110in
Zento L-170 RF AFT-TRx	P0200349	yes		2/2,4m 78/94in	2,4/3m 94/118in
Zento L-150 RF Tx/Rx	P0200291/*2			3/3,4m 118/134in	3,8/4,2m 150/165in
N-Line (Normal)					
Zento N-150 Light RF AFT-TRx	P0200389	yes		1,8/2,2m 70/86in	2,2/2,6m 86/102in
Zento N-150 RF Tx/Rx	P0200297/*8			2,8/3,2m 110/126in	3,6/4m 140/157in
Zento N-150 RF AFT-TRx	P0200353	yes		1,8/2,2m 70/86in	2,2/2,6m 86/102in
S-Line (Slim)					
Zento S-170 RF AFT-TRx	P0200368	yes		1,2/1,6m 47/62in	1,6/2m 62/78in
Zento S-170 RF AFT-TRX ISSH	P0200367	yes	yes	1,1/1,5m 43/59in	1,4/1,8m 55/70in



ADVERTISING INSERT SIZE

	# Product No.	Height	visible height	Width	visible width
L-Line (Large)					
Zento L-150 RF AFT-TRx	P0200352	1265mm	1246mm	450mm	434mm
Zento L-170 RF AFT-TRx	P0200349	1465mm	1446mm	450mm	434mm
Zento L-150 RF Tx/Rx	P0200291/*2	1265mm	1246mm	450mm	434mm
N-Line (Normal)					
Zento N-150 Light RF AFT-TRx	P0200389	1228mm	1208mm	350mm	334mm
Zento N-150 RF Tx/Rx	P0200297/*8	1265mm	1246mm	350mm	334mm
Zento N-150 RF AFT-TRx	P0200353	1265mm	1246mm	350mm	334mm
S-Line (Slim)					
Zento S-170 RF AFT-TRx	P0200368	1410mm	1391mm	250mm	234mm
Zento S-170 RF AFT-TRX ISSH	P0200367	1410mm	1391mm	250mm	234mm



Zento L-170 RF AFT-TRx

P0200349

General Info

Family	Zento
Size	Large
Type	TRx mono system

Recommendation 4x4 paper label

metric	imperial
Norm/Max Distance*	2/2,4m 78/94in
Norm/Max On side*	1/1,2m 39/47in

Recommendation round hardtag

metric	imperial
Norm/Max Distance*	2,4/3m 94/118in
Norm/Max On side*	1,2/1,5m 47/59in

Dimension

Height	1,726m	68in
Width	0,511m	20in
Depth (thickness)	0,061m	2.4in
Approx. weight	12kg	26.4lbs

Electrical Requirements

PSU	18V AC
Power Consumption	7W
Operating Temp.	0 - 40 °C 32 - 104 ° F

Other

Antenna Safety	CB, UL/cUL
Emissions Safety	FCC/IC, CE
Materials Used	aluminium side, plastic insert and body

*detection distance may vary, depends on **environment** and **tag type**.



RMS
by shopguard

Tx/Rx duo

TRx Alternating Field



Available colours



dark grey

Integrated Cashier Antenna RF AFT-TRx

Contact us!

General Info	
Family	Other
Type	TRx system with shield on one side (on cashier side)

Recommendation 4x4 paper label	metric	imperial
Norm/Max Distance*	1,6/2m	78.74in
Norm/Max On side*	0.8/1m	39.37in
Recommendation round hardtag	metric	imperial
Norm/Max Distance*	2,4/2,8m	110.23in
Norm/Max On side*	1,2/1,4m	47.24in
Dimension		
Height	1,606m	63.23in
Width	0,328m	12.92in
Depth (thickness)	0,106m	4.17in
Approx. weight	12,2kg	26.84lbs

Electrical Requirements		
PSU	18V AC	
Power Consumption	10W	
Operating Temp.	0 - 40 °C	32 - 104 °F

Other	
Antenna Safety	CB, UL/cUL
Emissions Safety	FCC/IC, CE
Materials Used	steel frame, plastic body

*detection distance may vary, depends on **environment** and **tag type**.



RMS
by shopguard



Tx/Rx duo

TRx Alternating Field