

Networking / Switches / Unmanaged

TK-TSW040

TELTONIKA



Features

- Teltonika
- Industrial Unmanaged PoE Switch
- Slim form factor
- 8 Ethernet RJ45 Gigabit ports
- 8 PoE+ Ports 802.3af/at
- Up to 30W per port
- Total PoE power 240W
- Plug and Play
- DC power connector of 2 industrial power supply pins
- DC 5 to 57V
- Status LEDs
- Ruggedized

Specifications

Brand	Teltonika
Device	Industrial Unmanaged PoE Switch
Ethernet	8 Ethernet ports RJ45 10/100Mbps
PoE ports	8 PoE+ Ports 802.3af/at
IEEE standards compliance 802.3	802.3i, 802.3u, 802.3ab, 802.3x, 802.3az
Switching capability (non-blocking)	20Gbps
MAC Table	2K inputs
Packet Buffer	128 Kb
Jumbo Frame	9216 bytes
Technology	Auto MDI/MDI-X Cable detection
Power	DC connector 2 Industrial pins 7 to 57v
Power consumption	Standby: 0,5W / Max: 1,5W / Max with PoE: 246 W
Power supply Protection	Overvoltage protection: 60 Vmax Reverse polarity protection: 80 Vmax Surge protection: min. 64,4 V/max. 71,2 V Input voltage range breakdown voltage, 93,6 V of maximum reverse voltage @4,3 A of maximum reverse surge current.
Material	Anodized Aluminum
Degree of protection	IP30
Temp. operation	-40° C ~ +75° C
Operating humidity	10 ~ 90 % (non-condensing)
Optional Mounting Kit (Not included)	Rail Mounting Kit
Dimensions	41,2 (Al) x 113,1 (W) x 74,6 (D) mm
Weight	280 g