

Networking / Switches / Unmanaged

TK-TSW010

TELTONIKA



Features

- Teltonika
- Industrial Unmanaged Switch
- Slim form factor
- 5 Ethernet RJ45 Gigabit ports
- Plug and Play
- DC power connector of 2 industrial power supply pins
- DC 9 to 30V or Passive PoE input on Ethernet port 1
- Status LEDs

Specifications

Brand	Teltonika
Device	Industrial Unmanaged Switch
Ethernet	5 Ethernet ports RJ45 10/100Mbps
IEEE standards compliance 802.3	802.3i, 802.3u, 802.3x, 802.3az
Switching capability (non-blocking)	1Gbps
MAC Table	2K inputs
Packet Buffer	128 Kb
Jumbo Frame	2048 bytes
Technology	Auto MDI/MDI-X Cable detection
Power	DC connector 2 Industrial pins 9 to 30v PoE In passive on Ethernet Port 1
Power consumption	Standby: 0,3W / Max: 0,9W
Material	Aluminium
Degree of protection	IP30
Temp. operation	-40° C ~ +75° C
Operating humidity	10 ~ 90 % (non-condensing)
Optional Mounting Kit (Not included)	Rail Mounting Kit
Dimensions	27,4 (Al) x 113,1 (W) x 80,5 (D) mm
Weight	146,5 g