



BRAVO INTR Wireless Control Panel

Description

BRAVO INTR is a wireless control panel with built-in power supply unit. The panel is suitable for intruder alarm security and protection of small home and residential sites.

Up to 16 wireless detectors BRAVO series (PIR, MC, FL and FD) can be enrolled to the panel as every detector represents security of one zone in the site. The BRAVO INTR panel is easy for installation, maintenance and operation, providing to the user two arming modes (Full and Partial), and also remote programming and management via MobileTTE smart phone application.

BRAVO INTR wireless control panel is designed according the requirements and covers the standard EN50131, GRADE 2.

Tel.:+359 2 9694 800

Fax: +359 2 9625 213

Technical Specifications

Power supply 100-240VAC; 50-60Hz

Backup power supply (battery). $1 \times 3.7 \text{V}/4000 \text{mAh}$, Li-Po type

Functional Specifications

- Quick and easy installation in the protected site
- Tamper switch for self-protection of the box
- Reset jumper for restoring the factory settings
- •LED indication for zone and system status
- •16 zones
- •8 remote key fobs
- •1 built-in and 1 outdoor siren
- •256 memory log events
- •2 slots for mounting of optional communication modules

Programming

- ProsTE software
- AjaxWEB user interface

Management

- MobileTTE smart phone application
- AjaxWEB user interface
- Contact Information







BRAVO INTR Wireless Control Panel

Packing Information

- Single packing box 1 unit BRAVO INTR, dimensions 225 x 167 x 50 mm
- Master packing box 12 units BRAVO INTR, dimensions 500 x 367 x 230 mm

BRAVO KIT SFTS

BRAVO INTR wireless panel is available in kit set with a range of wireless devices prepared for direct mounting in the protected site without need of enrolment and other settings. The kits set includes various devices and modules as option. For more information about the BRAVO kit contents ask for details your local distributer.

Compatible Product Range

- •BRAVO PIR Wireless passive infrared motion detector
- BRAVO MC Wireless magnetic contact
- BRAVO FL Wireless flood detector
- BRAVO FD Wireless fire alarm combined (optical-smoke and heat) detector
- •BRAVO RC Key-fob remote control
- •BRAVO SR200 Wireless outdoor sounder (115dB)
- •BRAVO SR300 Wireless outdoor sounder (110dB)
- BRAVO GPRS GPRS communication module
- BRAVO PSTN PSTN communication module
- •BRAVO PSTN VD PSTN communication module with voice messaging
- BRAVO MOUT Communication module with outputs (for connection of radio transmitter and PGM control)

Operation Diagram



- GPRS Teletek Electronics communication module and AJAX SP are a must for Mobile TTE.
- Availability for 24-hour monitoring and intuitive user interface via AJAX SP Cloud Service web application.

GPRS Module PSTN Module



Monitoring Center

Contact Information

Tel.:+359 2 9694 800 Fax: +359 2 9625 213