



BRAVO PSTN VDCommunication Module with Voice Dialer

Description

BRAVO PSTN VD is a communication module with dialer for voice messaging. The module is designed for operation in BRAVO wireless intruder alarm systems. The module is mounted into BRAVO panel via serial interface connection. The BRAVO PSTN VD module sends messages for events to 2 telephone numbers - to monitoring station (CID or SIA communication protocols) or directly to User (User communication protocol - audio call on Alarm only or Voice dialer). The module can be programmed via ProsTE software or AjaxWEB user web interface.



Technical and Functional Specifications

- · Built-in mounting in BRAVO panel
- · Serial interface connection on slot
- 4 telephone numbers for sending messages for events
- CID, SIA, User or Voice dialer communication protocols
- 2GB Micro SD card for storing voice messages
- User recording of the name for the protected site
- Voice guided remote management (arm, disarm) and report of system status over PSTN line
- · LED indication for PSTN line state
- PSTN terminals for connection of the line and telephone device
- Direct programming via ProsTE software
- Remote programming via AjaxWEB* software

Packing Information

• Single packing box - 1 unit BRAVO PSTN VD, dimensions 107 x 31 x 76mm

Compatible Product Range

- •BRAVO EXT Wireless panel with external power supply
- •BRAVO INTR Wireless panel with built-in power supply

Contact Information

^{*} AjaxWEB is part of Ajax Server installation.