



TTE Combo

Universal LAN/GPRS Communication Module

Description

TTE Combo is an universal module, that can be connected to any panel capable to transmit CID events. TTE Combo transmits those events to Ajax SP Pro server through LAN or GPRS network. TTE Combo is used to send alarm messages to monitoring center or end-user. The module is mounted in small plastic box suitable for wall mounting.

TTE Combo can also be used for remote management, programming and monitoring of the security system together with Eclipse panel and the AJAX SP PRO software application.

Technical Specifications

- Power supply 9-30 V DC
- Current Consumption:
 - Normal operation mode (Standby) 50 mA
 - Signal transmitting (GSM) max 1.6 A
- Programmable outputs 2, 100 mA, OC type
- Programmable inputs 1
- Encryption AES 128 bits
- Ethernet port 10/100Mbps
- Antenna connector (SMA) 50 Ohm



Functional Specifications

- Compatible with control panels capable to transmit Contact ID (CID);
- Control panel communication supervision;
- 2 Communication channels – LAN and/or GPRS;
- Main and Back-up reporting channels;
- Connecting to AJAX SP PRO through IP or DNS address;
- LAN settings – Manual or Automatic (DHCP);
- USB port for programming.

Packing Information

- **Single packing box** - 1 unit TTE Combo, dimension 108 x 108 x 46 mm
- **Carton packing box** - 62 units TTE Combo, dimensions 490 x 357 x 220 mm.

Compatible Product Range

- **Eclipse series** - Alarm control panels 8/ 16/ 32/ 99 zones
- **SB-U** - small universal box
- **Third party intruder alarm systems**

Contact Information