

# SF-TESTER4-5N1-4K

Multifunctional CCTV Tester  
Supports HDTV, HDCVI, AHD,  
CVBS and IP cameras  
Tester resolution up to 4K  
Colour LCD display 4"  
4000mA Built-in Battery  
Easy to use



## Safire

Multi-functional CCTV tester for HDTV, HDCVI, AHD, analogue CVBS and IP cameras

LCD 4" touch screen

Resolution 800x400

Decodes the camera image up to 8 MP (HDTV / HDCVI), 5 MP (AHD), 2 MP (CVBS) and 4K IP

Built-in WiFi

Audio inputs/outputs

PTZ analyser and controller. Supports multiple protocols

UTP Cable Tester

Digital multimeter

Rechargeable Lithium Battery 7.4V 4Ah

DC power supply outputs 12 V and PoE power supply

Multi-language menu

BNC Video Input/Output (Loop)

1 HDMI input

# Specifications

|                     |                                                                 |
|---------------------|-----------------------------------------------------------------|
| Brand               | SAFIRE                                                          |
| Screen              | IPS 4" resolution 800x480                                       |
| Formats             | HDTVI / HDCVI (4K) / AHD (5Mpx) / Analog CVBS (2Mpx) / IP (4K)  |
| Video settings      | Brightness, contrast and saturation                             |
| Inputs              | BNC (TVI/CVI/AHD/CVBS), RS485, 2x RJ45 (UTC/SCAN), HDMI, Audio  |
| Outputs             | 1xAudio, 1x12VDC / 2A, 1xPoE                                    |
| Analog video test   | Colour bar generator                                            |
| TDR Test            | YES (Only for cable RJ45)                                       |
| Digital Multimeter  | Voltage, Current, Resistance, Diode (Conductivity) and Capacity |
| PTZ                 | RS485                                                           |
| Communication       | WiFi, RJ45 10/100/1000M                                         |
| Cable Tester        | Independent accessory                                           |
| Power               | Lithium Battery 7.4 V 4000 mAh                                  |
| Charger             | DC 12V 3A                                                       |
| Temp. operation     | -10° C ~ +50° C                                                 |
| Dimensions / Weight | 240 mm x 123 mm x 38 mm / 600 g                                 |