

DV-MONOLITH-F

Duevi wired outdoor detector

Double PIR / Detection 15 m

Antimasking / Pet immunity

Power supply 9.6 ~ 14.5 VDC

Compatible with wired alarm systems

Outdoor use IP54 / Antivandalic IK10



Duevi

Wired outdoor detector

Double PIR

Anti-masking technology

Detection: Range 15 m / 90°

Motion detection indicator

Tamper-resistant opening

Power supply 9.6~14.5 VDC

Compatible with wired alarm systems

Degree of protection IP54, vandal resistant IK10

Specifications

Brand	Duevi
Model	Monolith F
Technology	Double volumetric PIR
PIR lens	Both lenses horizontally adaptable up to 55°
Detection range	Configurable: 3 m to 15 m (in 6 levels) / 90°
Pet immunity	Available (installation height 1.2 ~ 1.3 m)
Installation height	From 1.2 m to 2.2 m
Masking	Available: from 0°C, always on (through App) or disabled
Sensitivity	Adjustable (3 levels)
Tamper-resistant opening	Available
Anti-sabotage tamper	Available (motion accelerometer)
LEDs indication	Alarm (blue) and Walk test (red): Upper IR / green: Lower IR / blue: alarm confirmation)
DIP Switch configuration	1- Walk-test (On/Off) 2- Alarm unification in one output (On/Off)
Configuration in detector (LEDs and buttons)	Sensitivity / Anti-masking / Anti-sabotage tamper / Mounting height / Pet immunity / Detection range (more info page). 9 manual in download section)
Additional configuration in App	Antimasking (from 0°C, always on or disabled) / Antimasking sensitivity / Sleep time (On/Off/Up to 60 s)
Configuration by App	DV-BTLINK module required and download View Sensor App (Android)
Wired outputs	Alarm, Tamper and Antimasking
Power	9.6 at 14.5 VDC
Temp. operation	-40 °C ~ +70 °C
Degree of protection	IP54, Antivandalic IK10
Dimensions	201 (H) x 79 (W) x 81 (D) mm