

Mobility / On-board equipment / Streamax / Cameras

ST-946C25-RJ45-POE

STREAMAX



Features

- Streamax
- IP Dome Camera
- Resolution 1080P
- 2.8 mm Lens
- Aviation plug, 6 Pins
- IR distance up to 8m
- Supports N9M protocol
- Integrated microphone
- RJ45 PoE

Specifications

| | |
|-------------------------------|--|
| Brand | Streamax |
| Image sensor | 1/2.8" Progressive Scan CMOS sensor |
| Resolution | 1080p (1920x1080) |
| Main Stream | 1080p @30FPS |
| Sub-Stream | VGA/D1/CIF @ 30FPS |
| Lens | 2.8 mm (H: 104°, V: 55°) |
| Minimum illumination | 0.05Lux (Color), 0 Lux with IR, F1.2 |
| Infrared lighting | 5 - 8 m |
| Shutter | 1/30s-1/10000 |
| Audio | Built-in microphone, up to 4 meters |
| Audio Coding | ADPCM / G.711A / G.711U / G726 |
| Network interface | RJ45 10/100M |
| Communication protocol | N9M |
| Network protocol | TCP/IP, HTTP, DHCP, NTP, FTP |
| Power | PoE (DC 24V) < 2w (day) < 3.5w (night) |
| Installation | Ceiling or wall |
| Temp. operation | -40° C ~ +70° C, 90% |
| Dimensions | 52.6 (D) × 96 (W) × 101.5 (H) mm |
| Degree of protection | IP67 |