

Mobility / On-board equipment / Streamax / Cameras

ST-946C25-RJ45

STREAMAX



Features

- Streamax
- IP Dome Camera
- Resolution 1080P
- 2.8 mm Lens
- IR distance up to 8m
- Supports N9M protocol
- Integrated microphone
- RJ45 PON (9-15V)
- Weatherproof IP65

Specifications

Brand	Streamax
Image sensor	1/2.8" Progressive Scan CMOS sensor
Resolution	1080p (1920x1080)
Main Stream	1080p @30FPS
Sub-Stream	VGA/D1/CIF @ 30FPS
Lens	2.8 mm (H: 104°, V: 55°)
Minimum illumination	0.05Lux (Color), 0 Lux with IR, F1.2
Infrared lighting	5 - 8 m
Shutter	1/30s-1/10000s
Audio	Built-in microphone, up to 4 meters
Audio Coding	ADPCM / G.711A / G.711U / G726
Network interface	RJ45 10/100M
Communication protocol	N9M
Network protocol	TCP/IP, HTTP, DHCP, NTP, FTP
Power	PON (DC 9-15V) < 2w (day) < 3.5w (night)
Installation	Ceiling or wall
Temp. operation	-40° C ~ +70° C, 90%
Dimensions	52.6 (D) × 96 (W) × 101.5 (H) mm
Degree of protection	IP65