

Mobility / On-board equipment / Streamax / Cameras

# ST-P3H-SM-V2

STREAMAX



## Features

---

- Streamax
- Overhead installation
- Master people counting camera

## Specifications

---

|                                       |   |
|---------------------------------------|---|
| <b>Sensor</b>                         | 1/2.8" CMOS   |
| <b>Resolution</b>                     | 1080p (1920 x 1080)   |
| <b>Lens</b>                           | 2.8 mm (H: 103°, V: 56°, D: 121°)   |
| <b>Electronic Shutter</b>             | 1/25 ~ 1/25.000s (auto)   |
| <b>Image enhancement</b>              | DWDR, BLC, ATW, AWB, Auto Gain, 3D DNR  |
| <b>S/N</b>                            | >50dB   |
| <b>Minimum Illumination</b>           | 0,01 Lux (IR OFF), 0 Lux (IR ON)  |
| <b>Infrared lighting</b>              | 10 -15 m  |
| <b>Connection interface</b>           | Aviation plug 6-Pines   |
| <b>Day / Night</b>                    | ICR IR Filter   |
| <b>Lens adjustment</b>                | Up: 15° , Down:107°   |
| <b>Audio</b>                          | Integrated microphone up to 5m  |
| <b>Power</b>                          | 12V DC, 200mA. 2.4W / PON   |
| <b>Operating temperature</b>          | -40°C ~ 70°C  |
| <b>Dimension</b>                      | 47.5(Fo) x 61 (W) x58 (H) mm  |
| <b>Weight</b>                         | 125 g   |
| <b>Functionality and connectivity</b> | Artificial Intelligence-based People Counting<br>* Can perform people counting on its own<br>** If the bus has a second door, a counting camera P3 Slave can be connected to it |
| <b>Installation</b>                   | Overhead  |