

Mobility / On-board equipment / Streamax / Cameras

# ST-P3S-SM-V2

STREAMAX



## Features

---

- Streamax
- AHD camera
- People counting - Slave type
- Does not perform people counting on its own
- Overhead installation

## Specifications

---

<b>Sensor</b>	1/2.8" CMOS
<b>Resolution</b>	1080p (1920 x 1080)
<b>Lens</b>	2.8 mm (H: 103°, V: 56°, D: 121°)
<b>Electronic Shutter</b>	1/25 ~ 1/25.000s (auto)
<b>Image enhancement</b>	DWDR, BLC, ATW, AWB, Auto Gain, 3D DNR
<b>S/N</b>	>50dB
<b>Minimum Illumination</b>	0,01 Lux (IR OFF), 0 Lux (IR ON)
<b>Infrared lighting</b>	10 -15 m
<b>Connection interface</b>	Aviation plug 4-Pines
<b>Day / Night</b>	ICR IR Filter
<b>Lens adjustment</b>	Up: 15° , Down:107°
<b>Audio</b>	Integrated microphone up to 5m
<b>Power</b>	12V DC, 200mA. 2.4W
<b>Operating temperature</b>	-40°C ~ 70°C
<b>Dimension</b>	47.5(Fo) x 61 (W) x58 (H) mm
<b>Weight</b>	125 g
<b>Functionality and operation</b>	Connects to a Host counting camera in order to cover people counting at the second door of the bus * If the bus has a third door, the camera on this door must be Host ** Cannot perform people counting on its own, always needs a people counting camera P3 Host
<b>Installation</b>	Overhead