

Mobility / On-board equipment / Streamax / Cameras

ST-P3S-LM

STREAMAX



Features

- Streamax
- AHD camera
- People counting - Slave type
- Does not perform people counting on its own
- Wall-mounted installation

Specifications

Sensor	1/2.8" CMOS
Resolution	1080p (1920 x 1080)
Lens	2.8 mm (H: 103°, V: 56°, D: 121°)
Electronic Shutter	1/25 ~ 1/25.000s (auto)
Image enhancement	DWDR, BLC, ATW, AWB, Auto Gain, 3D DNR
S/N	>50dB
Minimum Illumination	0,01 Lux (IR OFF), 0 Lux (IR ON)
Infrared lighting	10 -15 m
Connection interface	Aviation plug 4-Pines
Day / Night	ICR IR Filter
Lens adjustment	Up: 15° , Down:107°
Audio	Integrated microphone up to 5m
Power	12V DC, 200mA. 2.4W
Operating temperature	-40°C ~ 70°C
Dimension	47.5(Fo) x 61 (W) x58 (H) mm
Weight	125 g
Operation and compatibility	Connects to a Host counting camera in order to cover people counting at the second door of the bus * If the bus has a third door, the camera on this door must be Host ** Cannot perform people counting on its own, always needs a people counting camera P3 Host
Installation	On wall