

Mobility / On-board equipment / Streamax / Cameras

# ST-C29N-P

STREAMAX



## Features

---

- Streamax
- IP camera
- Resolution 1280x800
- 3mm lens
- 0Lux
- IR up to 20m
- DSM: Driver status monitoring
- Connector M12
- Suitable for vehicle embarkation
- Compatible with ADPLUS 2.0
- Waterproof IP67

## Specifications

---

<b>Brand</b>	Streamax
<b>Intelligence</b>	DSM: Driver status monitoring Fatigue, drowsiness, cell phone and smoking detection
<b>Sensor</b>	1/4" Sensor Global Shutter
<b>Resolution</b>	1280x800
<b>Lens</b>	3 mm (H: 76°, V: 44°)
<b>Shutter</b>	1/30 ~ 1/5.000s (auto)
<b>Compression</b>	H.265 / H.264
<b>Image enhancement</b>	DWDR, BLC, ATW, AWB, Auto Gain, 3D DNR
<b>S/N</b>	> 50dB
<b>Minimum Illumination</b>	0,1 Lux@F1.4 (IR OFF), 0 Lux (IR ON)
<b>Day / Night</b>	ICR IR Filter
<b>IR range</b>	20 m
<b>Video output</b>	1.0 Vp-p AHD
<b>Connection interface</b>	Aviation connector 6-Pines M12
<b>Installation</b>	On side pillar
<b>Compatibility</b>	ADPLUS, AIBOX 5.0 and recorders
<b>Power</b>	12V DC, 230mA. < 2.76W
<b>Operating temperature</b>	-40°C ~ 70°C, < 95%
<b>Protection Grade</b>	IP67
<b>Dimension</b>	95.6 (D) x 57.8 (W) x 50.8 (H) mm
<b>Weight</b>	410g