

Mobility / On-board equipment / Streamax / Cameras

ST-C29N-V

STREAMAX



Features

- Streamax
- IP camera
- Resolution 1280x800
- 3mm lens
- 0Lux
- IR up to 20m
- DSM: Driver status monitoring
- Connector M12
- Suitable for vehicle embarkation
- Compatible with ADPLUS 2.0
- Vertical installation on dashboard
- Waterproof IP67

Specifications

Brand	Streamax
Intelligence	DSM: Driver status monitoring Fatigue, drowsiness, cell phone and smoking detection
Sensor	1/4" Sensor Global Shutter
Resolution	1280x800
Lens	3 mm (H: 76°, V: 44°)
Shutter	1/30 ~ 1/5.000s (auto)
Compression	H.265 / H.264
Image enhancement	DWDR, BLC, ATW, AWB, Auto Gain, 3D DNR
S/N	>50dB
Minimum Illumination	0,1 Lux@F1.4 (IR OFF), 0 Lux (IR ON)
Day / Night	ICR IR Filter
IR range	20 m
Video output	1.0 Vp-p AHD
Connection interface	Aviation connector 6-Pines M12
Installation	On side pillar
Compatibility	ADPLUS, AIBOX 5.0 and recorders
Power	12V DC, 230mA. <2.76W
Temperatura de funcionamiento	-40°C ~ 70°C, <95%
Grado de Protección	IP67
Dimensión	95.6 (Fo) x 57.8 (An) x 50.8 (Al) mm
Peso	410g