

UV-LINK-BOX

Uniview



Features

- Uniview IP camera configurator device
- Compatible with Uniview cameras for initial configuration
- 4 RJ45 (10M/100M Base-TX Ethernet inputs)
- Port 1 supports POE output (IEEE 802.3af)
- Port 4 supports PSE voltage detection (1V~56V; IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt) [%VAR%]
- WiFi 2.4G?(IEEE802.11b/g/n)
- Lithium battery 7500mAh
- DC power outputs 12V,1A/ 5V ,1A and USB-A
- With reset button

Specifications

Brand	Uniview
Battery Capacity	7500mAH (Lithium Battery 18650) (Lithium Battery [%VAR%])
Communication	WiFi, RJ45 10/100/1000M 4 X RJ45 10M/100M Base-TX Ethernet Port 1 supports POE (IEEE802.3af) Output Port 4 supports PSE Voltage Test
WiFi	2.4G Wi-Fi (IEEE802.11b/g/n)
Test Voltage	1 x PSE test Voltage (PSE voltage sensing range: 1V~56 V; IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt) 1 x DC test voltage (DC voltage detection range): 1V~56 V)
Input	1 x DC 5V/2A max, Type C
Output	1 x PoE Port (Powers a camera with the device's own battery) 1 x DC 12V/1A 1 x USB 5V/1A, TypeA
LED status indicator	System, WIFI and Battery
Temp. operation	-20?~60?, Humidity: ?95% RH
Dimensions / Weight	130 (A)× 85 (W)× 33 (D) mm