

Fire and Evacuation / Standalone / X-Sense

CO03D-W

X-SENSE



Features

- X-Sense
- Standalone carbon monoxide alarm
- Wireless communication 868MHz
- Allows multiple devices to be connected to sound at the same time
- Up to 24 interconnected detectors
- Alarm 85 dB to 3m
- Detection indicator light
- LCD screen with carbon monoxide measurement
- Test button
- Power supply 3 AA batteries 1.5 V
- Replaceable battery
- Certified EN 50291

Specifications

| | |
|--|--|
| Brand | X-Sense |
| Detector type | Electrochemical CO sensor |
| Wireless communication | RF 868MHz |
| Maximum number of connected devices | 24 |
| Certification | EN 50219 |
| CO Sensitivity | 50ppm: 60-90 minutes 100ppm:10-40 minutes 300ppm:3 minutes |
| Coverage range | 20m ² |
| Standby current | ?20 uA |
| Current in alarm | ?50 mA |
| Sound power | ?85dB to 3m |
| Detector life | 10 years |
| Battery | 3x AA 1.5 V (replaceable) |
| Operating temperature | 4.4~37.8°C |
| Operating Humidity | ?85% RH |
| Dimensions | 14.5 (Ø) x 5 (h) mm |