

Mobility / Trackers / Teltonika

# TK-FMB130

TELTONIKA



## Features

- Teltonika
- Tracker for vehicles
- Installation of internal vehicle wiring
- Connectivity 2G (GSM/GPRS) and Bluetooth LE 4.0
- GNSS positioning
- Internal antennas
- Micro-SIM + eSIM and Micro-USB slot 2.0
- LED indicators
- Digital and analog inputs and outputs
- Power supply DC 10-30 V
- Integrated battery
- Integrable with AIKO fleet management platform
- AIKO-LICENSE required for use
- SIM card required for use

## Specifications

---

<b>Brand</b>	Teltonika
<b>Model</b>	FMB130
<b>Installation</b>	Connection of internal vehicle wiring
<b>Positioning</b>	GNSS: GPS, GLONASS, GALILEO, BEIDOU, QZSS, AGPS
<b>Mobile connectivity</b>	2G (GSM/GPRS)
<b>Bluetooth connectivity</b>	BLE 4.0 for TK-EYE
<b>Interface connections</b>	1 x Micro-SIM + eSIM, 1 x Micro-USB 2.0 (configuration)
<b>Indicators</b>	Status and connectivity LEDs
<b>Sensors</b>	Accelerometer
<b>Inputs</b>	3 x Digital Input (2 configurable to Analog Input): negative and impulse 1 x CAN adapter input 1 x Input 1-Wire
<b>Outputs</b>	3 x Digital Output
<b>Functions</b>	Efficient driving, Overspeed, Forced shutdown, Collision detection, Energy-saving modes, Immobilizer, Anti-inhibit
<b>Configuration and management</b>	FOTA Web, Teltonika Configurator (USB and BLE)
<b>Power</b>	DC 10-30 V with overvoltage protection Built-in Li-Ion 3.7 V / 170 mAh battery
<b>Material</b>	Plastic
<b>Protection</b>	Suitable for indoor use (IP41)
<b>Temp. operation</b>	-40 °C ~ +85 °C
<b>Operating humidity</b>	5% ~ 95% (no condensation)
<b>Dimensions</b>	65 (W) x 56.6 (H) x 20.6 (D) mm
<b>Vehicle management</b>	Suitable for integration with AIKO fleet management platform
<b>Recommended scenarios</b>	Fleet management, Heavy vehicles, Refrigerated vehicles, Vehicle pooling