

XS-NVR3232-4K

X-Security NVR for IP cameras

Maximum resolution 8 Megapixel

Compression H.265 / H.264

32 CH IP

Outputs 4K HDMI & VGA

WEB, DSS/PSS, Smartphone and
NVR



X-Security

NVR for IP cameras

32 CH

200 Mbps bandwidth supported

Maximum resolution 8 Megapixel

Compression H.265 / H.264

Alarms

VGA and HDMI 4K output

IP Dual Stream Access

Mouse

Space for 2 HDD

WEB, CMS (DSS/PSS), Smartphone and NVR interface

ONVIF Compatible

Specifications

Brand	X-SECURITY
Inputs for IP cameras	LAN port up to 32 channels
PoE	No
IP compatible cameras	X-SECURITY (proprietary protocol), HIKVISION, SAFIRE, ONVIF
Video outputs	1 HDMI 4K, 1 VGA
Bidirectional audio	1 input, 1 output, RCA
Video compression format	H.265 / H.264
Display resolution	3840× 2160, 1920× 1080, 1280× 1024, 1280× 720, 1024× 768
Total bandwidth	200 Mbps
Recording resolution	8Mp, 6Mp, 5Mp, 3Mp, 1080P, 1.3Mp, 720P ...
Simultaneous multifunction	Pentaplex: Live, Recording, Playback, Backup and Remote Access
Alarms	No
Recording method	Manual, programmed, motion detection, alarm
Backup	USB (Memory, HDD, CD-RW, DVR-RW) / Network / SATA
Internal memory	2 SATA HDD 3.5" of up to 6 TB (not included)
Communication	2xUSB (Mouse & backup) / 1 RJ45 10/100/1000M (Ethernet)
Remote access	Web browser (ActiveX), mobile phone application or PSS software
Power	DC 12 V / 4.0 A
Dimensions	56 (H) x 282 (W) x 375 (D) mm / 1.6 Kg (without HDD)